



**Container Stacker**

**Application Area:**

- ✍ Cement Industries.
- ✍ Fertilizer Industries.
- ✍ Food Industries.
- ✍ Chemical Industries.
- ✍ Railway Loading.
- ✍ Warehouses & Cold Storage. and other process industries.



**Standard Conveyor**



**Container Stacker (Dual)**



**Low-Intake Conveyor.**

**An Unique Equipment to assist in Loading, Unloading, Stacking & De-stacking of Bags, Boxes etc.**



**Telescopic Table Conveyor**

TYPE	Model	Length	Feeding Height	Discharge Height	Belt , Bed Width
		(in mm)	(in mm)	(in mm)	(in mm)
TABLE CONVEYOR	TC-6 , 8 , 12 , 15	6000 - 15000	850	850 - 1250	500 , 600
	TC-3, 7 (Retractable)	3000 - 11000	850	850 - 1250	500 , 600
STANDARD CONVEYOR	MLS-4.5, 6 , 8	4500 - 8000	850	1200 - 4500	500 , 600
	MLS- 10 , 12	10000 - 12000	850	1200 - 6000	500 , 600
RETRACTABLE STANDARD CONVEYOR	MLS- 3.0, 5.0	3000 - 8000	850	1200 - 3800	500 , 600
	MLS- 7.0	6500 - 11250	850	1200 - 4200	500 , 600
CONTAINER STACKER	CS-3.0 , 5.0, 7.0	7000 - 14000	300 - 3300	1200 - 5600	500 , 600
	CS-3.0 (Dual)	7000 - 10000	200 - 4400	200 - 4400	500 , 600

**OTHER STANDARD AND OPTIONAL FEATURES**

1. Power requirement of 2 - 6 HP (Three Phase).
2. Reversible belt for facilitating both loading and unloading or stacking and de-stacking.
3. Load bearing capacity of upto 200 Kg. Loading capacity of upto 50 Tons/hr.
4. Push button Driving Unit for smooth shifting of the equipment. (Optional)
5. Custom designing of the feeding and discharge height of the equipment.