



Container Stacker

Application Area:

- ✍ Cement Industries.
- ✍ Fertilizer Industries.
- ✍ Food Industries.
- ✍ Chemical Industries.
- ✍ Railway Loading.
- ✍ Warehouses & Cold Storage. and other process industries.



Standard Conveyor



Container Stacker (Dual)



Low-Intake Conveyor.

An Unique Equipment to assist in Loading, Unloading, Stacking & De-stacking of Bags, Boxes etc.



Telescopic Table Conveyor

| TYPE | Model | Length | Feeding Height | Discharge Height | Belt , Bed Width |
|-------------------------------|-----------------------|---------------|----------------|------------------|------------------|
| | | (in mm) | (in mm) | (in mm) | (in mm) |
| TABLE CONVEYOR | TC-6 , 8 , 12 , 15 | 6000 - 15000 | 850 | 850 - 1250 | 500 , 600 |
| | TC-3, 7 (Retractable) | 3000 - 11000 | 850 | 850 - 1250 | 500 , 600 |
| STANDARD CONVEYOR | MLS-4.5, 6 , 8 | 4500 - 8000 | 850 | 1200 - 4500 | 500 , 600 |
| | MLS- 10 , 12 | 10000 - 12000 | 850 | 1200 - 6000 | 500 , 600 |
| RETRACTABLE STANDARD CONVEYOR | MLS- 3.0, 5.0 | 3000 - 8000 | 850 | 1200 - 3800 | 500 , 600 |
| | MLS- 7.0 | 6500 - 11250 | 850 | 1200 - 4200 | 500 , 600 |
| CONTAINER STACKER | CS-3.0 , 5.0, 7.0 | 7000 - 14000 | 300 - 3300 | 1200 - 5600 | 500 , 600 |
| | CS-3.0 (Dual) | 7000 - 10000 | 200 - 4400 | 200 - 4400 | 500 , 600 |

OTHER STANDARD AND OPTIONAL FEATURES

1. Power requirement of 2 - 6 HP (Three Phase).
2. Reversible belt for facilitating both loading and unloading or stacking and de-stacking.
3. Load bearing capacity of upto 200 Kg. Loading capacity of upto 50 Tons/hr.
4. Push button Driving Unit for smooth shifting of the equipment. (Optional)
5. Custom designing of the feeding and discharge height of the equipment.